






EU 0561A

Lamierini tranciati - Macchine asincrone

SA073C CPK

RA037C CPK

DE mm	DI mm	N	A mmq	LD mm	LC mm	LS mm	AC mm
73,00	38,00	24	28,92	2,15	9,50	0,00	1,80

de mm	n	a mmq	ld mm	ac mm
37,30	18	20,78	2,00	0,00

#	RI	GR	SA	MT	PT	RF	V	P _{1mm} g
1				✓		✓		18,21
2				✓		✓	✓	18,15
3						✓	✓	17,6
4						✓		17,6

#	di mm	pz	c	l	fv	ri	P _{1mm} g
1	8						5,17
2	14						4,36
3	14,98						4,19
4	17						3,79



LEGENDA ROTORE - sezione A

de	Diametro esterno
di	Diametro interno
n	Numero cave
a	Area cava
ld	Larghezza dente
ac	Apertura cava
pz	Pozzetto
c	Scanalatura per chiavetta
l	Foro lobato
fv	Fori di ventilazione
ri	Fori per rivetti
P _{1 mm}	Peso indicativo g per 1 mm/sp.

This image shows a full page of blank graph paper. The grid consists of small, uniform squares formed by thin, light gray lines. There are no margins, text, or other markings on the page.