



EU 0150C Lamierini tranciati - Motori a poli schermati

SS061C CPK

| DE mm | DI mm | LU mm | LA mm | LI mm | PB mm | $\alpha 1$ ° | $\alpha 2$ ° |
|-------|-------|-------|-------|-------|-------|--------------|--------------|
| 0,00 | 29,85 | 61,00 | 61,00 | 48,00 | 32,10 | 20,00 | 50,00 |

| # | RI | PT | NF | CP | RF | $P_{1\text{mm}}$ g |
|---|----|----|----|----|----|--------------------|
| 1 | | ✓ | ✓ | | | 13,63 |

TS061C CPK

| DI mm | L mm | S mm |
|-------|------|-------|
| 0,00 | 37,1 | 14,10 |

| # | RI mm | $P_{1\text{mm}}$ g |
|---|-------|--------------------|
| 1 | | 3.90 |

RS029C CPK

| de mm | n | a mmq | ld mm | ac mm |
|-------|----|-------|-------|-------|
| 29,25 | 16 | 14,00 | 1,93 | 0,00 |

| # | di mm | pz | c | l | $P_{1\text{mm}}$ g |
|---|-------|----|---|---|--------------------|
| 1 | 4,5 | | | | 3,29 |
| 2 | 6 | | | | 3,19 |
| 3 | 8 | | | | 3,02 |
| 5 | 3,2 | | | | 3,35 |
| 6 | 5 | | | | 3,26 |

