



SF 0170C Lamierini tranciati - Motori a poli schermati

SS061A CPK

| DE mm | DI mm | LU mm | LA mm | LI mm | PB mm | $\alpha 1$ ° | $\alpha 2$ ° |
|----------|----------|----------|----------|----------|----------|-----------------|-----------------|
| 0,00 | 30,00 | 63,30 | 61,00 | 17,00 | 32,00 | 15,13 | 46,66 |

| # | RI | PT | NF | CP | RF | $P_{1\text{mm}}$ g |
|---|----|----|----|----|----|-----------------------|
| 1 | | ✓ | ✓ | | | 14,1 |

TS061A CPK

| DI mm | L mm | S mm |
|----------|---------|---------|
| 0,00 | 40,0 | 16,00 |

| # | RI mm | $P_{1\text{mm}}$ g |
|---|----------|-----------------------|
| 1 | | 4.70 |

RS029A CPK

| de mm | n | a mmq | ld mm | ac mm |
|----------|----|----------|----------|----------|
| 29,40 | 18 | 13,90 | 1,40 | 0,00 |

| # | di mm | pz | c | l | $P_{1\text{mm}}$ g |
|---|----------|----|---|---|-----------------------|
| 1 | 3,17 | | | | 2,7 |
| 2 | 4,5 | | | | 2,66 |
| 3 | 5 | | | | 2,64 |
| 4 | 6 | | | | 2,6 |
| 5 | 8 | | | | 2,52 |

